

**Jondaryan Rail Loading Facility Air Quality Monitoring Results**

Issue Month: April 2015



**NEW HOPE GROUP**

New Acland Coal Pty Ltd (NAC) undertakes air quality monitoring as part of the environmental monitoring program for the Jondaryan Rail Loading Facility (JRLF). The following air quality data is provided to the Jondaryan community.

**Table 1: Dust deposition and compositional monitoring results for the period: February 2015**

Site	Dust Deposition (mg/m <sup>2</sup> /day)	EA Criteria (mg/m <sup>2</sup> /day) <sup>#</sup>	Compositional Analysis <sup>†</sup>			Comments
			Major (>20%)	Minor (<20%>1%)	Trace (<1%)	
JD1	13.3	120	Mineral Material (50%), Coal (25%)	Insects (10%), Vegetation (10%), Polysaccharide Slime (5%)	NA	Rail and Highway to the north, north-west & north-east. JRLF to east. Grass and gravel immediately surrounding, stubble paddocks to north-east, east, south-east & south-west. Bare paddock to east. Residential to north and west. Road with unsealed edges to north-west, north & north-east, unsealed road to landfill to north-east & gravel driveways to west, north & north-east. Road to south-west, west, north-west & north.
JD2	16.6	120	Mineral Material (40%), Coal (40%)	Other Impurities (10%), Insects (5%), Vegetation (5%)	N/A	Rail and Highway to north, north-west & north-east. JRLF to the north-east. Grass immediately surrounding. Residential to south and west. Road with unsealed edges to north-east, east, south-east, south, south-west, north-west & north. Dirt road to south-east & south. Road to south-west, west, north-west, north-east.
JD3	26.6	120	Mineral Material (45%), Coal (30%)	Insects (10%), Vegetation (10%), Polysaccharide Slime (5%)	NA	Highway and Rail to north-west, north, north-east. JRLF to the east. Residential surrounding. Grass and garden immediately surrounding. Road to north, north-east, east, south-east. Road with unsealed edges to north, north-east, east, south-east, south, south-west. Gravel road to east. Crop paddock to south, south-west.
JD4	26.6	120	Mineral Material (50%), Coal (30%)	Insects (10%), Vegetation (10%)	N/A	Rail, Highway and Jondaryan town to south-east, south, south-west, west. JRLF to the east. Grass & crop paddock immediately surrounding. Roads to north-east, east, south-east, south, south-west. Road with unsealed edge to south-east & south.
JD5	20.0	120	Polysaccharide Slime (45%)	Coal (20%), Mineral Material (15%), Insects (10%), Vegetation (10%)	NA	Rail and Highway to north-west, north, north-east. JRLF to the north-east. Grass immediately surrounding. Gravel edge road to north, north-east, east, south-east. Residential to east, south and west. Crop paddock to south, south-west. Road to east, south-east.

<sup>†</sup> A semi-qualitative visual analysis of a representative portion of the collected sample which is as consistent as possible (however potentially biased) to that of the complete sample  
<sup>\*</sup> Copper sludge is a by product of the necessary preservative (copper sulphate) in sample containers as directed by the laboratory  
<sup>#</sup> Polysaccharide slime is a by product of the bio-degradation of insects and vegetation

<sup>#</sup> When measured at a sensitive place, the allowable maximum level of the release of dust from the JRLF is 120 milligrams per square metre per day (120mg/m<sup>2</sup>/day) as stated in the JRLF's Environmental Authority (EA). The dust deposition monitors do not distinguish between dust sources. The predominant wind directions for February 2015 were from the east (58.97%), south-east (25.52%), north-east 4.9% & south (3.92%). The predominant wind speed for February was calm to light winds.

**Table 2: Quarterly PM<sub>10</sub> monitoring result for the period 8-9 January 2015**

Location	24 Hour PM <sub>10</sub> Result (µg/m <sup>3</sup> )	Long-Term PM <sub>10</sub> Average (µg/m <sup>3</sup> )	NEPM Criteria for 24 Hour PM <sub>10</sub> exposure <sup>#</sup> (µg/m <sup>3</sup> )	Comments <sup>*</sup>
Corner of Lagoon and Earl Streets, Jondaryan	9	22	50	"This site was within the downwind area of coal stockpile for approximately 16% of the time"

<sup>\*</sup> Taken from monitoring report, with respect to most recent result  
<sup>#</sup> PM<sub>10</sub> monitoring is undertaken on a quarterly basis for a nominal 24 hour period.

The national 24-hour exposure standard for PM<sub>10</sub> particulates stated in the National Environment Protection Measure for Ambient Air Quality is 50 micrograms per cubic metre (50µg/m<sup>3</sup>). The PM<sub>10</sub> monitors do not distinguish between *particulate matter sources*.

February 2015 TEOM Results



**Figure 1: Jondaryan Township TSP continuous monitoring results for the period: February 2015**

**Comments:** A TEOM located within the Jondaryan Township continuously measures Total Suspended Particulate (TSP) matter. When measured at a sensitive place, the maximum level of the release of TSP from the JRLF (24-hour average) is 80 micrograms per cubic metre (80µg/m<sup>3</sup>) as stated in the JRLF's EA. The TEOM's do not distinguish between particulate matter sources. The predominant wind directions for February 2015 were from the east (58.97%), south-east (25.52%), north-east 4.9%, south (3.92%). The predominant wind speed for February was calm to light winds. The TEOM unit was operational for >99% of the sample period.

If there are any queries regarding the air quality monitoring undertaken for the Jondaryan Rail Loading Facility please contact Rob Rashleigh at the New Acland Coal Mine during business hours on 4694 8888.

Issued by:  
**Rob Rashleigh**  
 CHPP Manager  
 New Acland Coal Pty Ltd

Date: 20/04/2015